



Power HD

SAE 30,40, 50,60 API SC/CC

Power HD 40, 50, 60 is mono - grade engine oil formulated from excellent quality base stocks with superior additives package. It is suitable for gasoline and diesel engines in both heavy duty and stop and go service. By meeting the API standard specification it provides excellent engine protection, superior thermal stability with the quality of anti wear and detergency.

BENEFITS

- ◆ Provides highest engine protection
- ◆ Prolongs drain interval
- ◆ Ensures minimum maintenance cost
- ◆ Ensures smooth engine operation.



TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS		
		SAE 40	SAE 50	SAE 60
ASTM Color	ASTM D 1500	L 2.5	L 2.5	L 2.5
Specific Gravity at 15 deg	ASTM D 1298	0.8926	0.8954	0.8986
Viscosity at 40 deg	ASTM D 445	157.89	207.6	310.67
Viscosity at 100 deg	ASTM D 445	15.01	18.25	23.65
Viscosity Index	ASTM D 2270	95	96	96
Pour Point	ASTM D 97	-12	-12	-9
Flash Point	ASTM D 92	238	258	248
TBN	ASTM D 5984	4.25	4.15	4.28

PERFORMANCE STANDARDS

API : SC/CC

Data Sheet